Fukushima Daiichi Nuclear Power Station Plant Parameters

reactor

S/C

[Note] Some indicators might not be functioning properly beyond the normal condition for usage affected by the earthquake and subsequent events. We comprehensively evaluate situation in plants using all the available information from indicators and also focusing on trends, taking uncertainty of indicators into consideration.

Unit 6

Stoppage range

2100mm

(as of 12:00, 12/11)

0.016 MPa g

(as of 12:00, 12/11)

26.5 ℃

(as of 12:00, 12/11)

As of 12:00 on December 11 Unit Unit 1 Unit 2 Unit 3 Unit 5 Unit 4 Fresh water feeding Fresh water feeding Fresh water feeding ※2 (Heat removal of the reactor is functioning, Water Status of water eed water system 4.2m3/h, CS line 2.0m3/h Feed water system 2.9m³/h, CS line 6.0m³/h Feed water system 3.0m³/h, CS line 6.0m³/h injection is unnecessary) injection to the as of 11:00, 12/11) (as of 11:00, 12/11) (as of 11:00, 12/11) reactor Fuel range A: Downscale Fuel range A: Downscale ЖЗ Fuel range A:-1739 mm ЖЗ Stoppage range Water level in the -uel range B:-1500 mm Fuel range B-2112 mm жз Fuel range B-2222 mm жЗ 1808mm жз (as of 11:00, 12/11)(as of 11:00, 12/11)(as of 11:00, 12/11) (as of 12:00, 12/11) System A:Downscale System A:0.003 MPa g System A:0.008 MPa g (A) %3 0.010 MPa g Pressure in the System B:-MPa g System B:-MPa g System B: Downscale (C) ※3 reactor (as of 12:00, 12/11) (as of 11:00, 12/11) (as of 11:00, 12/11) (as of 11:00, 12/11) 26.5 ℃ Water temperature of (as of 12:00, 12/11) (Since there is no water inflow in the system it is impossible to collect the data) the reactor Temperature in feed-water nozzle:69.5 °C Temperature in feed-water nozzle:42.6 °C Temperature in feed-water nozzle:58.6 °C *2 Temperature at reactor vessel bottom:43.5 °C Temperature at reactor vessel bottom 74.5 °C Temperature at reactor vessel bottom 65.6 °C Temperature around %2 (monitoring through water temperature of the (Monitoring is (as of 11:00, 12/11) (as of 11:00, 12/11) (as of 11:00, 12/11) the reactor vessel reactor) unnecessary since all fuel are D/W:0.1102 MPa abs D/W:0.111 MPa abs D/W:0.1016 MPa abs takeoff) Pressure in D/W · S/C:0.082 MPa abs жЗ S/C: Downscale Ж1 S/C:0,1846 MPa abs (as of 11:00, 12/11) (as of 11:00, 12/11) (as of 11:00, 12/11) RPV bellow seal 72.8 °C RPV bellow seal:44,9 °C RPV bellow seal:69.6 °C жз ЖЗ D/W Atmosphere HVH return:46.3 °C HVH return:78.0 °C жз HVH return:59.6 °C temperature (as of 11:00, 12/11) (as of 11:00, 12/11) (as of 11:00, 12/11)

temperatore	(as of 11.00, 12/11)	(as of 11.00, 12/11)	(as of 11.00, 12/11)		* 0	
0.4440	D/W(A):1.00E-02Sv/h	D/W(A):7.11E+00Sv/h (B):2.85E+00Sv/h S/C(A):7.00E-02Sv/h (B):2.48E+00Sv/h (as of 11:00 , 12/11) (B):2.48E+00Sv/h (B):2.48E+00Sv/h	D/W(A):3,11E+00Sv/h %3 (B):2,09E+00Sv/h S/C(A):2,56E-01Sv/h (B):2,44E-01Sv/h (as of 11:00 , 12/11)		*2 (Monitoring is unnecessary reactor is functioning.)	v since heat removal of
Temperature in S/C	(as of 11:00 , 12/11)	System A:48.5 °C System B:48.3 °C (as of 11:00 , 12/11)	System A:37.2 °C System B:37.3 °C (as of 11:00 , 12/11)			
Designed usable D/W pressure	0.384MPa g (0.485MPa abs)	0.384MPa g (0.485MPa abs)	0.384MPa g (0.485MPa abs)			
Designed usable D/W maximum pressure	0.427MPa g (0.528MPa abs)	0.427MPa g (0.528MPa abs)	0.427MPa g (0.528MPa abs)	_	-	_
Temperature in the spent fuel pool	13.5 ℃ (as of 11:00 , 12/11)	28.9°C (as of 11:00 , 12/11)	14.4 ℃ (as of 11:00 , 12/11)	21℃ (as of 11:00 , 12/11)	18.2 ℃ (as of 12:00 , 12/11)	17.5 ℃ (as of 12:00 , 12/11)
FPC skimmer surge tank level	4030mm (as of 11:00 , 12/11)	3140mm (as of 11:00 , 12/11)	4260mm (as of 11:00 , 12/11)	3838mm (as of 11:00 , 12/11)	*2	
Power source	Receiving offsite power (P/C2C)		Receiving offsite power (P/C4D)		Receiving offsite power	
Others	 Hydrogen concentration by Primary Containment Vessel (PCV) gas management system, Unit 2: 0.6vol% (as of 11:00, 12/11) HVH return temperature of Unit 2 D/W is "under continuously monitoring" as the cause is under investigation after the confirmation of possibility of defect. We have made a correction of an expression in "Others" of the plant parameters document which we announced as of 6:00 am on November 10 to 6:00 am on December 11 in the following manner: Before correction: Hydrogen concentration by Pressure Containment Vessel (PCV) gas management system → After correction: Hydrogen concentration by Primary Containment Vessel (PCV) 			Temperature in the Common Spent Fuel Storage: 18°C (as of 9:50, 12/11)	5u : SHC mode (from 14:24 ,12/6)	6u : SHC mode (from 11:18 ,12/9)

Pressure conversion Gauge pressure (MPa g) = Absolute pressure (MPa abs) - atmospheric pressure (normal atmospheric pressure(.1013 MPa) Absolute pressure (MPa abs) = Gauge pressure (MPa g) + atmospheric pressure (normal atmospheric pressure0.1013 MPa)

%1 : Instrument failure %2 : Not covered for colleting data

*3 : continuously monitoring the status

Fukushima Daiichi Nuclear Power Station Supplemental explanation for the plant parameters

■Supplemental explanation for each parameter

ltem	Recording manner	Measurement manner	Ch number or number of systems	
Status of water injection to the reactor	Water inflow (CS line : Core Spray system)	Temporary	System 1 / 1	
Water level in the reactors	Data measured by the water gauge, which monitor the fuel range	Temporary	System A 1/1Ch System B 1/1Ch	
Pressure in the reactor	One representing value is noted among multiple data on each System A, B. Readings of temporary instruments are represented in A system for Unit 1and 2.	Temporary	1 ∕ 1 system (Unit 1/2) System A 1 ∕ 2Ch, System B 1 ∕ 2Ch (Unit 3)	
Temperature in the reactor	Since there is no water inflow at the points, where thermometers are set, no data is collected.	—	_	
Temperature around the reactor vessel	Data measured at feed-water nozzle and at reactor vessel bottom (1U, 3U : RPV Bottom Head, 2U : RPV Wall Above Bottom Head) are noted among multiple data to view the whole picture.	Temporary	Point of Feed-water nozzle 1/4Ch reactor vessel bottom 1/2Ch (Unit1) 1/1Ch (Unit2/3)	
Pressure in D/W • S/C	Data from temporary instrument. (D/W:Dry Well、S/C:Suppression Chamber)	Temporary	(D/W) wide range 1/1Ch (Unit 1) 1/4Ch (Unit 2/3) (S/C) 1/1system (Unit 1/2) 1/2Ch (Unit 3)	
	Data at upper point (RPV Bellows Air) and middle point (HVH return) are noted among multiple data to view the whole picture. (RPV : Reactor Pressure Vessel、HVH : Heating Ventilating Handling Unit)	Temporary	RPV Bellows Air 1 / 5Ch D/W HVH return 1 / 5Ch	
CAMS radiation monitor	Data from temporary instrument. (CAMS : Containment Atmospheric Monitoring System)	Temporary	D/W System A 1/1Ch System B 1/1Ch S/C System A 1/1Ch System B 1/1Ch	
Temperature in S/C	Data from temporary instrument. One representing value is noted among multiple data on each System A, B.	Temporary	System A1/4Ch (Unit 1) 、8Ch (Unit 2/3) System B1/4Ch (Unit 1) 、8Ch (Unit 2/3)	
Temperature in the spent fuel pool	Data from temporary instrument. (Non-thermal mode : Urgent Heat load Mode、SHC mode : Shut down Cooling Mode)	Temporary	1 / 1 Ch (Unit 2) 1 / 1 system (Unit 1/3/4)	
FPC skimmer surge tank level	 Unit2, 4 are the FPC skimmer surge tank level measured temporary instrument, Unit1, 3 are the FPC skimmer surge tank level estimated from temporary pressure gages,(reference value) (FPC : Fuel Pool Cooling system) 	Temporary	1/1system	

■Supplemental explanation for notes

ltem	Contents	Status As of 12:00 on December 11		
Instrument failure	Instrument failure : down of instrument reading (over) scale/failure of instrument	Unit 1 CAMS D/W radiation monitor Unit 2 Pressure in S/C, CAMS D/W(B) radiation monitor, CAMS S/C(B) radiation monitor Unit 3 $-$		
Not covered for collecting data	Unit4: Monitoring is not implemented since all fuel are takeoff. Unit5/6: Monitoring is not implemented since heat removal of reactor is functioning	-		
Continuously monitoring the status	Inaccurate Data defined from relation with other Parameters such as negative figure.	Unit 1 Reactor water level(B), Pressure in S/C Unit 2 Reactor water level, RPV bellow air temperature,HVH return temperature Unit 3 Reactor water level, reactor pressure, RPV bellow air temperature, CAMS D/W(A) radiation monitor		