Situation of water level, transfer and treatment of the accumulated water in Fukushima Daiichi Nuclear Power Station (at 9:00 on January 24)

	Water level of Vertical Shaft	Unmeasurable due to drawdown of water level			
		(Less than O.P.+ 850 mm)	O.P.+ 3,093 mm (45 mm decrease since 16:00 on January 23)	O.P.+ 3,073 mm (4 mm increase since 16:00 on January 23)	_
Water Level of the accumulated water (at 7:00 on January 24)	Water level of Turbine Building	O.P.+ 2,652 mm (11 mm increase since 16:00 on January 23)	O.P.+ 3,068 mm (39 mm decrease since 16:00 on January 23)	O.P.+ 3,020 mm (48 mm increase since 16:00 on January 23)	O.P.+ 3,008 mm (2 mm decrease since 16:00 on January 23)
	Water level of Reactor Building	O.P.+ 4,339 mm (16 mm decrease since 16:00 on January 23)	O.P.+ 3,226 mm (48 mm decrease since 16:00 on January 23)	O.P.+ 3,299 mm (39 mm increase since 16:00 on January 23)	O.P.+ 3,027 mm (7 mm increase since 16:00 on January 23)
	Water level of each building in the Centralized Radiation Waste Treatment Facility	Process Main Building High Temperature Incinerator Building On-site Bunker Building	O.P.+ 3,772 mm (Increase from initial level:4,989 mm, 85 mm decrease since 16:00 on January 23) O.P.+ 2,995 mm (Increase from initial level:3,721 mm, 143 mm increase since 16:00 on January 23) O.P.+ 4,361 mm (Water level from floor:565 mm, 14 mm increase since 16:00 on January 23)		
Situation of transfer of the accumulated water		Transfer suspended	Basement of Unit 2 Turbine Building →Centralized Radiation Waste Treatment Facility (High Temperature Incinerator Building) Currently being transferred (Since 14:33 on January 22)	Transfer suspended	_
Operation condition of water treatment facility		Cesium Adsorption Apparatus: Since 18:45 on January 17 In operation 2nd Cesium Adsorption Apparatus (Sarry): Since 8:35 on January 24 Suspended Water Desalination Apparatus (reverse osmosis membrane): Intermittent operation depending on the water balance Water Desalination Apparatus (evaporative concentration): Intermittent operation depending on the water balance			
Notes	As there is a gradual lo	lowering of throughput of the second cesium adsorption adsorption apparatus (Sarry), it is temporarily stopped to backwash its filter.			